

# OPT-EMAX D400

- Ductile Iron
- EN124 Class D (400kN)
- AS3996 Class E
- Non-ventilated
- Advanced hinge design
- Easy access and installation
- Highest standards of safety and performance
- Maximum durability in arduous conditions
- Anti-theft, anti-vandal design with optional locking kits



Reference	Description		Heaviest Cover (Kg)	Dimensions mm		
	Type	Frame		Clear Opening	Depth	Overbase (mm)
<b>NORMAL TRAFFIC</b>						
BA02 1	Non-ventilated	Rectangular	22.3	600 x 450	100	806 x 650
BA06 1	Non-ventilated	Square	26.2	600 x 600	100	800 x 800
BA22 1	Non-ventilated	Square	40	675 x 675	100	875 x 875
H524 1	Non-ventilated	Rectangular	39	750 x 600	100	940 x 745
H510 1	Non-ventilated	Square	43.3	750 x 750	100	905 x 940
BA54 1	Non-ventilated	Rectangular	40.7	900 x 600	100	1100 x 800
H530 1	Non-ventilated	Rectangular	51.4	1060 x 700	100	1210 x 850
BA78 1	Non-ventilated	Rectangular	38	1220 x 685	100	1380 x 885
H564 1	Non-ventilated	Rectangular	39	1200 x 750	100	1350 x 945
H571 1	Non-ventilated	Rectangular	43	1500 x 750	100	1660 x 940
H584 1	Non-ventilated	Rectangular	39	1800 x 750	100	1955 x 940

OPT-EMAX Accessories	
187096	Opt-Emax Lock M12 Hex Head SS + Instruction
190664	Opt-Emax Key M12