


- Ductile Iron
- EN124 Class D (400kN)
- AS3996 Class E
- Hinged
- Springbar locking mechanism
- Ventilated and non ventilated options



Reference	Description		Mass (in kg)		Dimensions mm		
	Type	Frame	Total	Cover	Clear Opening	Height	Frame Size
CDKO60EF	Non ventilated	Round	62	38	606	104	841
CDKO60EFX15*	Non ventilated	Round	62	38	606	104	841
CDKO60EF-ST (stormwater)	Non ventilated	Round	62	38	606	104	841
CDKO60EF-SW (sewer)	Non ventilated	Round	62	38	606	104	841
CDKO60EF-SWFISH (stormwater fish)	Non ventilated	Round	62	38	606	104	841
CDKO60EF-WW (waste water)	Non ventilated	Round	62	38	606	104	841
CDKO60FF-WW (waste water)	Ventilated	Round	62	38	606	104	841

* Includes D50 Lock



Ductile iron anti-theft spline
Prevents the cover from being extracted and stolen. It can be installed after the cover is installed

Note: accessories are painted yellow for illustration purposes only.



Anti-intrusion lock :
The lock D50, features a ductile cast iron bar, with high resistance to prevent unauthorised entry.

KORUM Accessories	
CDKO60BF-J	KORUM Blue Elastomer Ring
C38	KORUM Anti Theft Spline
C46	KORUM Opening Key for D50 Lock
C47	KORUM Lock
SGKORUM-IMP	KORUM Safety Grill 1000kg Load Tested
CDKO600SCP	KORUM Stainless Steel Catchpan to suit Ventilated